

CLAIMS

1 1. Fountain pump with a housing, which has a housing wall, which is
2 constructed at least partially as a filter, through which the water can flow into the housing;
3 with a first outlet, through which the water can be pumped out of the housing; with a
4 suction connection; with a pumping device for sucking in water and for discharging water;
5 and with a control unit for controlling the pumping device, characterized by the fact that at
6 least one additional filter element (17) is detachably mounted on the housing (3).

1 2. Fountain pump in accordance with Claim 1, characterized by the fact that the
2 additional filter element (17) is hinged on the housing (3) in such a way that the filter
3 element (17) rests against the wall (3.2, 3.3) of the housing (3) in a first position and is
4 swung away from the wall (3.2, 3.3) of the housing (3) like wings in a second position.

1 3. Fountain pump in accordance with Claim 1 or Claim 2, characterized by the fact
2 that the housing (3) has a longitudinal axis, and the housing wall (3.2, 3.3), which is
3 constructed as a filter, is arranged parallel to the longitudinal axis.

1 4. Fountain pump in accordance with Claim 3, characterized by the fact that the
2 housing wall (3.2, 3.3), which is constructed as a filter, has two filter surfaces, which are
3 arranged parallel to the longitudinal axis and each other and symmetrically about the
4 longitudinal axis.

1 5. Fountain pump in accordance with Claim 4, characterized by the fact that an
2 additional filter element (17) is hinged on the housing (3) in such a way that it rests against
3 each filter surface (3.2, 3.3) in the first position and is swung away from each filter surface
4 (3.2, 3.3) like wings in the second position.

1 6. Fountain pump in accordance with any of Claims 1 to 5, characterized by the
2 fact that the additional filter element (17) is hinged on the upper side of the housing (3).

1 7. Fountain pump in accordance with any of Claims 1 to 6, characterized by the
2 fact that the additional filter element (17) has an outside and an inside, each of which is
3 designed as a filter surface.

1 8. Fountain pump in accordance with any of Claims 1 to 7, characterized by the
2 fact that the additional filter element (17) has a connection (17.4) for a hose coupling with
3 the suction connection (11), so that the additional filter element (17) remains connected
4 with the housing (3) even when it is separated from the housing.

1 9. Fountain pump in accordance with any of Claims 1 to 8, characterized by the
2 fact that a second outlet (13) is formed on the housing (3).

1 10. Fountain pump in accordance with any of Claims 1 to 9, characterized by the
2 fact that the additional filter element (17) has a control element (9) for adjusting a
3 waterworks function at an outlet (7, 13) of the housing (3).

1